

Well-Worth
PROFESSIONAL PERFORMANCE PRODUCTS

Well-Worth Products, Inc.
180 Dutton St.
Buffalo, NY, 14211
USA

PRODUCT: Out of Sight - 20 oz.

CODE: 1057

Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Item Numbers..... 1057
 Product Identity..... Out of Sight - 20 oz.
 Supplier..... Well-Worth Products, Inc.
 180 Dutton Ave.
 Buffalo, NY
 USA 14211
 wellworthproducts.com
 Tel: 800-890-7935
 Fax: 716-597-0217
 24 hour emergency telephone number..... CHEM TREC: 800-424-9300.
 Recommended Use..... Cleans windows, mirrors, windshields, tile, porcelain, stainless steel, chrome.
 Chemical Family..... Mixture.

Section 02: HAZARDS IDENTIFICATION



Hazard Classification:
 Physical Hazards..... Gases Under Pressure - Liquefied Gas . Aerosols - Category 3.
 Health Hazards..... Eye Damage/Irritation - Category 2B.
 Environmental Hazards..... Acute Aquatic Hazard - Category 3.
 Label Elements:
 Signal Word..... WARNING.
 Hazard Statement..... Pressurized container: may burst if heated. Contains gas under pressure; may explode if heated. Causes eye irritation. Harmful to aquatic life.
 Precautionary Statements:
 Prevention..... Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wash thoroughly after handling. Avoid release to the environment .
 Response..... IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 Storage..... Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F .
 Disposal..... Dispose of contents/ container in accordance with local/regional/national/international regulations.
 Hazard(s) not otherwise classified (HNOC).. None Known.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
Isobutane	75-28-5	5-10
Isopropyl Alcohol	67-63-0	1-5
Acetone	67-64-1	1-5
2-Butoxyethanol	111-76-2	1-5
Ammonia Solution	7664-41-7	0.1-1

Section 04: FIRST AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
 Skin Contact..... Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.
 Eye Contact..... Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.
 Ingestion..... If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.
 Most important symptoms/effects, acute and delayed Direct eye contact may cause temporary eye irritation.

PRODUCT: Out of Sight - 20 oz.

CODE: 1057

Section 04: FIRST AID MEASURES

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Section 05: FIRE FIGHTING MEASURES

Suitable Extinguishing Media.....

Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

Unsuitable Extinguishing Media.....

Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special Protective Equipment and Precautions for Firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

General Fire Hazards.....

Flammable.

Section 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment and Cleaning Up

Spill areas may be slippery. Use care to avoid falls or other accidents. Contain the spill. Clean up the spill area with detergent and water. Once spilled material has been collected, use rags or other suitable material to clean spill area. Rags should be properly disposed of.

Environmental Precautions.....

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Section 07: HANDLING AND STORAGE

Precautions for Safe Handling.....

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients	ACGIH TLV		PEL	OSHA PEL		REL	NIOSH
	TWA	STEL		STEL	STEL		
Isobutane	800 ppm	1000 ppm	800 ppm	Not available	800 ppm (TWA)		
Isopropyl Alcohol	400 ppm (983 mg/m3)	500 ppm (1230 mg/m3)	400 ppm (980 mg/m3)	500 ppm (1,225 mg/m3)	400 ppm (TWA)		
	400 ppm						
Acetone	500 ppm	750 ppm	Not available	1000 ppm	Not available		
2-Butoxyethanol	20 ppm	Not available	50 ppm	Not available	Not available		
Ammonia Solution	25 ppm	35 ppm	50 ppm	Not available	25 ppm		
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.						
Individual Protection Measures:							
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.						
Skin Protection.....	Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.						
Respiratory Protection.....	Use NIOSH approved respirator suitable for organic vapours.						
Thermal Hazards.....	None Known.						
General Hygiene Considerations.....	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.						

PRODUCT: Out of Sight - 20 oz.

CODE: 1057

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

Form.....	Aerosol.
Physical Appearance.....	Cloudy liquid .
Odor.....	Fragrance.
Odor Threshold (ppm).....	N/A.
Specific Gravity	0.970-0.990.
Aerosol Vapour Pressure (psig, 21°C).....	60-80.
Vapour Density (Air=1).....	> 1.
pH.....	10.5-11.0.
Boiling Point liquid (°C).....	100°C (212°F).
Melting/Freezing Point (°C).....	N/A.
Flash Point (°C), Method.....	None.
Flashback.....	No.
Evaporation Rate (n-Butyl Acetate = 1).....	Slow.
VOC Content.....	12%.
Solubility in water.....	Soluble.
Aerosol Flame Projection.....	No data.
Auto Ignition Temperature (°C).....	460°C (860°F). (For propellant).
Lower Flammable Limit (% Vol).....	1.4. (For propellant).
Upper Flammable Limit (% Vol).....	8.5. (For propellant).
Coefficient of Water/Oil Distribution.....	N/A.
Viscosity.....	N/A.

Section 10: STABILITY AND REACTIVITY

Reactivity	Product not reactive under normal conditions of use.
Chemical Stability.....	Material is stable under normal conditions.
Possibility of Hazardous Reactions.....	Will not occur.
Conditions to Avoid.....	Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials.....	Strong oxidizing agents.
Hazardous Decomposition Products.....	Carbon Oxides.

Section 11: TOXICOLOGICAL INFORMATION

Ingredients	LC50	LD50
Isobutane	658 mg/L (4hrs,Rat)	Not available
Isopropyl Alcohol	>20,000 ppm (4hrs-rat)	4,700 - 5,800 mg/kg (oral,rat)
Acetone	32000 ppm (Rat,4hr)	5,800 mg/kg (Oral,Rat)
2-Butoxyethanol	74.9 mg/L (Inhalation,Rat,3hr)	1,300 mg/kg (Oral,Rat); 2,000 mg/kg (Dermal,Rat)
Ammonia Solution	2,000 (rat- 4hrs)	Not applicable
Information on Likely Routes of Exposure:		
Routes of entry - Inhalation.....	Prolonged inhalation may be harmful.	
Routes of entry - Skin & Eye.....	Direct contact with eyes may cause temporary irritation.	
Routes of entry - Ingestion.....	Expected to be a low ingestion hazard.	
Routes of entry - Skin Absorption.....	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.	
Symptoms Related to the Physical, Chemical and Toxicological Characteristics		
Acute Toxicity.....	Skin contact may cause irritation. Irritating to the eyes. Harmful or fatal if swallowed.	
Skin Corrosion/Irritation.....	Causes mild skin irritation. Prolonged contact may be more irritating.	
Serious Eye Damage/Eye Irritation.....	Direct contact with eyes causes temporary irritation.	
Respiratory or Skin Sensitization.....	Not expected to be a skin or respiratory sensitizers.	
Germ Cell Mutagenicity.....	No data available to indicate product or any components present at greater than 0.1% are mutagenic.	
Carcinogenicity.....	2-Butoxyethanol (CAS#: 111-76-2): ACGIH-A3 Confirmed animal carcinogen with unknown relevance to humans; IARC-3 Not Classifiable as to carcinogens to humans.	
Reproductive Toxicity.....	Contains no ingredient listed as toxic to reproduction.	
Specific Target Organ Toxicity - Single Exposure	Not classified.	
Specific Target Organ Toxicity - Repeated Exposure	Not classified.	
Aspiration Hazard.....	Not classified.	
Chronic Effects.....	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.	

PRODUCT: Out of Sight - 20 oz.

CODE: 1057

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	Harmful to aquatic life. Should not be released into the environment. This product contains the following ingredients: . Isopropanol alcohol (CAS#: 67-63-0): Toxicity to fish: LC50 9,640 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 5,102 mg/L, 96 hrs; Toxicity to algae: EL50 >2,000 mg/L, 72 hrs. Ammonia Solution (CAS#: 7664-41-7): Toxicity to fish: LC50 0.16- 1.1mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EC 50 25.4 mg/L, 48 hrs; Toxicity to algae: EC50 >2,700 mg/L, 432 hrs. Acetone (CAS#: 67-64-1): Toxicity to fish: LC50 >100 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 10294 mg/L, 48 hrs; Toxicity to algae: not available .
Persistence and degradability	The product itself has not been tested.
Bioaccumulation Potential.....	The product itself has not been tested.
Mobility in Soil.....	The product itself has not been tested.
Other Adverse Effects.....	None Known.

Section 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods.....	Empty containers may be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with current local, provincial and federal regulations.
-----------------------------------	--

Section 14: TRANSPORT INFORMATION

TDG (Canada- Road).....	AEROSOLS, Class 2.2, UN1950.
DOT (US-Road).....	AEROSOLS, Class 2.2, UN1950, LTD QTY, Consumer Commodity ORM-D.
IMDG (International- Marine).....	AEROSOLS, Class 2.2, UN1950.
IATA (International- Air).....	AEROSOLS, Class 2.2, UN1950, LTD QTY .

Section 15: REGULATORY INFORMATION

Canada Regulations:.....	WHMIS Classification. A: Compressed gas. D2B: Material causing other toxic Materials.
Canadian Environmental Protection Act (CEPA)	All ingredients listed appear on the Domestic Substances List (DSL).
US Regulations.....	Environmental Protection Act: Constituents of this product are included on the TSCA inventory.
OSHA.....	This product is considered hazardous under the Federal OSHA hazard communication standard.
California Proposition 65.....	This product does not contain any chemical(s) known to the state of California to cause cancer or reproductivity toxicity.

Section 16: OTHER INFORMATION

Disclaimer.....	The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.
Abbreviations.....	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHIMIS: Workplace Hazardous Materials Information System.
Prepared by	Regulatory Affairs
Preparation Date.....	Feb04/15