



Well-Worth Products, Inc.
180 Dutton St.
Buffalo, NY, 14211
USA

PRODUCT: Laser Penetrating Oil - 16 oz.

CODE: 5011

Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Item Numbers..... 5011
 Product Identity..... Laser Penetrating Oil - 16 oz.
 Supplier..... Well-Worth Products, Inc.
 180 Dutton Ave.
 Buffalo, NY
 USA 14211
 wellworthproducts.com
 Tel: 800-890-7935
 Fax: 716-597-0217
 24 hour emergency telephone number..... CHEM TREC: 800-424-9300.
 Recommended Use..... Penetrating oil.
 Chemical Family..... Mixture.

Section 02: HAZARDS IDENTIFICATION



Hazard Classification:
 Physical Hazards..... Flammable Aerosols - Category 1 . Gases Under Pressure - Compressed gas.
 Health Hazards..... Specific Target Organ Toxicity, Single Exposure - Category 3. Specific Target Organ Toxicity, Repeated Exposure - Category 2. Skin Irritation - Category 2. Eye Damage/Irritation - Category 2B. Aspiration Hazard - Category 2. Toxic to Reproduction - Category 2.
 Environmental Hazards..... Chronic Aquatic Hazard - Category 3.
 Label Elements:
 Signal Word..... DANGER.
 Hazard Statement..... Extremely flammable aerosol. Pressurized container: may burst if heated. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. May be harmful if swallowed and enters airways. May cause damage to the liver and kidneys through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.
 Precautionary Statements:
 Prevention..... Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment.
 Response..... IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER if you feel unwell. IF ON SKIN: Wash with plenty of soap and water . If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF SWALLOWED: Immediately call a POISON CENTER. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage. If exposed or concerned: Get medical advice/attention.
 Storage..... Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F . Store in a well-ventilated place. Keep container tightly closed. Store locked up.
 Disposal..... Dispose of contents/ container in accordance with local/regional/national/international regulations.
 Hazard(s) not otherwise classified (HNOC).. None Known.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
Solvent Naphtha, Heavy Aliphatic	64742-96-7	30-60
Isopropyl Alcohol	67-63-0	10-30
2-Butoxyethanol	111-76-2	3-7

PRODUCT: Laser Penetrating Oil - 16 oz.

CODE: 5011

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Xylene	1330-20-7	10-30
Surfactants	Proprietary	1-5
Carbon Dioxide	124-38-9	1-5

Section 04: FIRST AID MEASURES

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
Skin Contact.....	Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.
Eye Contact.....	Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.
Ingestion.....	Ingestion is unlikely to occur. If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Section 05: FIRE FIGHTING MEASURES

Suitable Extinguishing Media.....	Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
Unsuitable Extinguishing Media.....	Do not use water jet as an extinguisher, as this will spread the fire.
Specific Hazards Arising from the Chemical.	In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified Organic Compounds.
Special Protective Equipment and Precautions for Firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
General Fire Hazards.....	Extremely flammable aerosol.

Section 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).
Methods and Materials for Containment and Cleaning Up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.
Environmental Precautions.....	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Section 07: HANDLING AND STORAGE

Precautions for Safe Handling.....	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.
Conditions for Safe Storage including any Incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Solvent Naphtha, Heavy Aliphatic	Not available	Not available	Not available	Not available	Not available	Not available
Isopropyl Alcohol	400 ppm (983 mg/m3)	500 ppm (1230 mg/m3)	400 ppm (980 mg/m3)	500 ppm (1,225 mg/m3)	400 ppm (TWA)	

PRODUCT: Laser Penetrating Oil - 16 oz.

CODE: 5011

Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
	400 ppm				
2-Butoxyethanol	20 ppm	Not available	50 ppm	Not available	Not available
Xylene	100 ppm	150 ppm	100 ppm (435 mg/m ³)	150 ppm (655 mg/m ³)	Not established
Surfactants	Not available	Not available	Not available	Not available	Not available
Carbon Dioxide	5000 ppm	30000 ppm	9000 mg/m ³	Not available	STEL: 30000ppm; TWA: 5000ppm
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.				
Individual Protection Measures:					
Eye/Face Protection.....	Chemical splash goggles are recommended.				
Skin Protection.....	Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.				
Respiratory Protection.....	Use dust and mist respirator.				
Thermal Hazards.....	None Known.				
General Hygiene Considerations.....	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.				

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

Form.....	Aerosol.
Physical Appearance.....	Yellowish liquid .
Odor.....	Characteristic solvent odor .
Odor Threshold (ppm).....	N/A.
Specific Gravity	0.820-0.850.
Aerosol Vapour Pressure (psig, 21°C).....	75-95.
Vapour Density (Air=1).....	Heavier than air.
pH.....	N/A.
Boiling Point liquid (°C).....	82.5°C (180.5°F). Estimated.
Melting/Freezing Point (°C).....	N/A.
Flash Point (°C), Method.....	11.7°C (53°F) Closed Cup.
Flashback.....	N/A.
Evaporation Rate (n-Butyl Acetate = 1).....	> 1 .
VOC Content.....	97%.
Solubility in water.....	Nil.
Aerosol Flame Projection.....	N/A.
Auto Ignition Temperature (°C).....	>315°C (>599°F).
Lower Flammable Limit (% Vol).....	0.7.
Upper Flammable Limit (% Vol).....	12.7.
Coefficient of Water/Oil Distribution.....	N/A.
Viscosity.....	N/A.

Section 10: STABILITY AND REACTIVITY

Reactivity	Product not reactive under normal conditions of use.
Chemical Stability.....	Material is stable under normal conditions.
Possibility of Hazardous Reactions.....	Will not occur.
Conditions to Avoid.....	Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials.....	Keep away from heat. Strong oxidizing agents.
Hazardous Decomposition Products.....	See Section 05.

Section 11: TOXICOLOGICAL INFORMATION

Ingredients	LC50	LD50
Solvent Naphtha, Heavy Aliphatic	>2000 mg/cu.m (4hr, rat)	>8000 ml/kg (Oral, Rat)
Isopropyl Alcohol	>20,000 ppm (4hrs-rat)	4,700 - 5,800 mg/kg (oral, rat)
2-Butoxyethanol	74.9 mg/L (Inhalation, Rat, 3hr)	1,300 mg/kg (Oral, Rat); 2,000 mg/kg (Dermal, Rat)
Xylene	5000 ppm (4 hrs)	4300 mg/kg
Surfactants	Not available	Not available
Carbon Dioxide	Not available	Not available

PRODUCT: Laser Penetrating Oil - 16 oz.

CODE: 5011

Section 11: TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure:

Routes of entry - Inhalation.....	Yes.
Routes of entry - Skin & Eye.....	Yes.
Routes of entry - Ingestion.....	Yes.
Routes of entry - Skin Absorption.....	Yes.
Symptoms Related to the Physical, Chemical and Toxicological Characteristics	
Acute Toxicity.....	Harmful or fatal if swallowed. Irritating to the eyes,nose and throat. Skin contact may cause irritation.
Skin Corrosion/Irritation.....	Causes skin irritation.
Serious Eye Damage/Eye Irritation.....	Causes eye irritation.
Respiratory or Skin Sensitization.....	May cause sensitization by skin contact. Inhalation may cause respiratory tract irritation.
Germ Cell Mutagenicity.....	No data available to indicate product or any components present at greater than 0.1% are mutagenic.
Carcinogenicity.....	2-Butoxyethanol (CAS#: 111-76-2): ACGIH-A3 Confirmed animal carcinogen with unknown relevance to humans; IARC-3 Not Classifiable as to carcinogens to humans. Xylene (CAS#: 1330-20-7): ACGIH A4 Not Classified as a human carcinogen; IARC 3 Not classifiable as to carcinogenicity to humans.
Reproductive Toxicity.....	Xylene (CAS#:1330-20-7): Causes fetotoxic effects (e.g., reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data.
Specific Target Organ Toxicity - Single Exposure	Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness.
Specific Target Organ Toxicity - Repeated Exposure	Specific Target Organ, Repeated Exposure- Category 2. May cause damage to the liver and kidneys through prolonged or repeated exposure.
Aspiration Hazard.....	Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.
Chronic Effects.....	Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment.. Isopropanol alcohol (CAS#: 67-63-0): Toxicity to fish: LC50 9,640 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 5,102 mg/L, 96 hrs; Toxicity to algae: EL50 >2,000 mg/L, 72 hrs. Xylene (CAS#:1330-20-7): Toxicity to fish: 780.0 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EC50 0.8 mg/L , 48 hrs; Toxicity to algae: EC50 10.0mg/L.
Persistence and degradability	The product itself has not been tested.
Bioaccumulation Potential.....	The product itself has not been tested.
Mobility in Soil.....	The product itself has not been tested.
Other Adverse Effects.....	None Known.

Section 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods.....	This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.
-----------------------------------	---

Section 14: TRANSPORT INFORMATION

TDG (Canada- Road).....	AEROSOLS, Class 2.1, UN1950.
DOT (US-Road).....	AEROSOLS, Class 2.1, UN1950, LTD. QTY. OR ORM-D.
IMDG (International- Marine).....	AEROSOLS, Class 2.1, UN1950.
IATA (International- Air).....	AEROSOLS, Class 2.1, UN1950, LTD QTY.

Section 15: REGULATORY INFORMATION

Canada Regulations:.....	WHMIS Classification. A: Compressed gas. B5: Flammable Aerosol. D2A: Material causing very toxic effect. D2B: Material causing other toxic Materials.
Canadian Environmental Protection Act (CEPA)	All ingredients listed appear on the Domestic Substances List (DSL).
US Regulations.....	Environmental Protection Act: Constituents of this product are included on the TSCA inventory.
OSHA.....	This product is considered hazardous under the Federal OSHA hazard communication standard.
California Proposition 65.....	This product does not contain any chemical(s) known to the state of California to cause cancer or reproductivity toxicity.

PRODUCT: Laser Penetrating Oil - 16 oz.

CODE: 5011

Section 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHIMIS: Workplace Hazardous Materials Information System.

Prepared by Regulatory Affairs
Preparation Date..... Mar30/15